


PERMANENT MOUNT

Wireless Hand-Held Remote
20004 (white) 20514 (black)


Hard-Wired Dash Mount Remote
20204 (white) 20214 (black)



Wireless Hand-Held &
Wireless Dash-Mount Remotes
20074 (white) 20574 (black)

PORTABLE MODELS

Suction Cup & Permanent Shoe
Wired Remote - 51494 (charcoal)
Wireless Remote - 79004 (white)




PORTABLE MODELS

Suction Cup & Magnetic Shoe
Wireless Hand-Held Remote
79014 (white) 79514 (black)



Golight RadioRay LED
Light Beam Dimensions



Illuminance (Lux) 656 164 41 10

Peak Beam Intensity: 410,000 Candela
Maximum Beam Distance: 1,280 m / 4,200 ft
Beam Angle: 8°



3 Year Warranty	 Quality Checked
 Hor. & Vert. Rotation	 Weather Resistant
 Low Maintenance	 Low AMP Draw
 UV Resistant	 Remote Control

Housing:	Heat resistant and high impact injection molded housing
	ASA Polymer (white housing) ABS Polymer (black housing)
Parts:	Nylon, Acetal Rack O-ring, Stainless Steel pinion drive
	15' 18G cord with universal cigarette lighter plug
Fasteners:	Stainless Steel
Motors:	Automotive grade 12V D.C. High Torque, R.P.M. 6087
	Constant Torque 17.333mN.m/amp, Stall: 12.31 mN.m Draw point 4 amps
	Output: 1.96 watts w/built in stall protection circuitry
	Built in stall protection circuitry
Quality and Type of LED's:	10 High Flux LED's
	P-Vex lens technology
	8° beam angle
	Anodized Aluminum heat sink w/liquid powder-cast finish
Peak Beam Intensity:	410,000 Candela
Max Beam Distance:	4,200 ft
Voltage DC:	12V
Power Consumption:	40W
Max Current Draw:	3 amps
Wireless Remote Control:	Radio Frequency: 433 MHz
	> 2000 possible address codes with 7 station dip switch
	Transmitter power: 2 Duracell MN21 12v batteries
	Radio Frequency allows for remote operation up to 80 feet away
Hardwired Dash Mount Remote:	On/Off switch, 4 way toggle
	20' of six wire cord
Warranty:	3 Year Limited Warranty
Mounting Options:	Permanent Mount, Portable Light/Magnetic Shoe, Portable Light/Permanent Shoe
Rockguard:	Not Available for LED Models