




Stryker Hardwire - LED

37146 Old Hwy 17 - Culbertson, NE 69024 | 800.557.0098 | golight.com



PERMANENT MOUNT MODELS

Hard Wired Dash Mount Remote


30204 (white)

30264 (chrome)

30214 (black)



LED Light Beam Dimensions



Illuminance (Lux) 870 218 55 14

Peak Beam Intensity: 544,000 Candela

Maximum Beam Distance: 1,475 m / 4,839 ft

Beam Angle: 8°



5 Year Warranty	 Quality Checked
 Hor. & Vert. Rotation	 Weather Resistant
 Low Maintenance	 Low AMP Draw
 UV Resistant	 Remote Control

Housing:	ASA Luran heat resistant High impact, UV resistant material
Gears & Transmission Parts:	Lexan and Brass
Fasteners:	Stainless Steel
Motors:	Automotive grade 12V D.C. High Torque, R.P.M. 6087 Constant Torque 17.133 mN.m/amp, Stall:12.31 mN.m Draw point 4 amps Output: 1.96 watts w/built in stall protection circuitry Built in stall protection circuitry
Type and Quality of LED's:	10 High Flux LED's P-Vex lens technology 8° beam angle Anodized Aluminum heat sink w/liquid powder-cast finish
Peak Beam Intensity:	544,000 Candela
Max Beam Distance:	4,839 ft.
Voltage DC:	12V
Power Consumption:	40W
Max Current draw:	3.7 amps
Wired Remote Control:	Hard Wired Dash Remote Multi Speed Capability Joystick Control
Warranty:	5 Year Limited Warranty
Mounting Options:	Permanent Mount Only
Rockguard:	Not available for LED Styker Models