

Golight/RadioRay 5149/51494

37146 Old Hwy 17 - Culbertson, NE 69040 | 800.557.0098 | golight.com



PORTABLE MODELS

Suction Cup & Permanent Shoe


Wired Remote

51494 (LED)

5149 (Halogen)



Halogen Light Beam Dimensions



Illuminance (Lux) 360 90 25 6


Peak Beam Intensity: 225,000 Candela

Maximum Beam Distance: 949 m / 3,113 ft

Beam Angle: 8°



LED Light Beam Dimensions



Illuminance (Lux) 870 218 55 14

Peak Beam Intensity: 544,000 Candela

Maximum Beam Distance: 1,475 m / 4,839 ft

Beam Angle: 8°



| | |
|-------------------------------------|---|
| Housing: | Heat resistant and high impact injection molded housing |
| | ASA Polymer (white housing) ABS Polymer (black housing) |
| Parts: | Nylon, Acetal Rack O-ring, Stainless Steel pinion drive |
| | 15' 18 Gauge cord with universal cigarette lighter plug |
| Fasteners: | Stainless Steel |
| Motors: | Automotive grade 12V D.C. High Torque, R.P.M. 6087 |
| | Constant Torque 17.333mN.m/amp, Stall: 12.31 mN.m Draw point 4 amps |
| | Output: 1.96 watts w/built in stall protection circuitry |
| | Built in stall protection circuitry |
| Quality and Type of LED's: | 10 High Flux LED's |
| | P-Vex lens technology |
| | 8° beam angle |
| | Anodized Aluminum heat sink w/liquid powder-cast finish |
| LED Peak Beam Intensity: | 544,000 Candela |
| LED Max Beam Distance: | 4,839 ft |
| LED Voltage DC: | 12V |
| LED Power Consumption: | 40W |
| LED Max Current Draw: | 3.7 amps at 13.8V |
| Halogen Peak Beam Intensity: | 225,000 Candela |
| Halogen Max Beam Distance: | 3,113 ft |
| Halogen Voltage DC: | 12 |
| Halogen Power Consumption: | 5.5 amps at 13.8V |
| Remote: | Inline with on/off switch and |
| | 4 way directional control |
| Warranty: | 3 Year Limited Warranty |
| Mounting Options: | Permanent Mount Shoe, Suction Cup |
| Rockguard: | Available for Halogen Models only |