Styker ST Series - Halogen

37146 Old Hwy 17 - Culbertson, NE 69040 | 800.557.0098 | golight.com



PERMANENT MOUNT MODELS

Wireless Handheld Remote

3000ST (white) 3006ST (chrome) 3051ST (black)

Hardwired Dash Control


3020ST (white) 3026ST (chrome) 3021ST (black)

PORTABLE MODELS (Magnetic Base) Wireless Handheld Remote 30002ST (white)

30062ST (chrome) 30512ST (black)



Halogen Light Beam Dimensions



Peak Beam Intensity: 225,000 Candela Maximum Beam Distance: 949 m / 3,113 ft Beam Angle: 8°





Housing:	ASA Luranheat resistant
	High Impact, UV resistant material
Gears & Transmission Parts:	Lexan and Brass
Fasteners:	Stainless Steel
Motors:	Automotive grade 12V D.C. High Torque, R.P.M. 6087
	Constant Torque 17.133 mN.m/amp, Stall: 12.31 mN.m Draw point 4 amps
	Output: 1.96 watts w/built in stall protection circuitry
	Built in stall protection circuitry
Lamp / Cr5 II Pentabeam :	Phillips H9 (Bulb (est. 270 life hours)
Peak Beam Intensity:	225,000 Candela
Max Beam Distance:	3,113 ft.
Reflector:	Computer generated parabolic
Voltage DC:	12V
Power Consumption:	65W
Max current draw:	5.5 amps
Wireless Remote Controls:	Radio Frequency: 2.4 GHz, Code match pairing process, Batteries: 2 AAA
	Lamp On/Off, Directional Controls, Home Command, Spotlight Selector (1,2), Speed Selector
Hardwired Control:	Lamp On/Off, Directional Controls, Home Command, Spotlight Selector (1,2), Speed Selector
Warranty:	5 Year Limited Warranty
Mounting Options:	Permanent Mount or Portable Magnetic Base
Rockguard:	Included with all Halogen Styker Models