
GT SERIES - LED SPOT

37146 Old Hwy 17 - Culbertson, NE 69024 | 800.557.0098 | golight.com





PERMANENT MOUNT Wireless Handheld Remote 20004GT (white) 20514GT (black)

Hardwired Dash Mount Remote 20204GT (white) 20214GT (black)

Wireless Handheld & Wireless Dash Mount Remotes 20074GT (white) 20574GT (black)

PORTABLE MODELS Permanent Shoe Wireless Remote - 79004GT (white)

PORTABLE MODELS

Magnetic Shoe Wireless Handheld Remote 79014GT (white) 79514GT (black)



LED SPOT Light Beam Dimensions

870	Lux	218	Lux	55	Lux	14 Lux	27(88 Beam W
m(ft) 25(82)	50(1	64)	100(328)	200(656)	

Illuminance (Lux) 870 218 55 14 Peak Beam Intensity: 544,000 Candela Maximum Beam Distance: 1,475 m / 4,839 ft Beam Angle: 8°

FL1 STANDARD	FL1 STANDARD
	La
	1475m
544,000cd	
	· · · · ·

ith



Housing:	Heat resistant and high impact injection molded housing
	ASA Polymer (white housing) ABS Polymer (black housing)
Parts:	Nylon, Acetal Rack O-ring, Stainless Steel pinion drive
	15' 18 AWG cord with universal cigarette lighter plug (Portable Units)
Fasteners:	Stainless Steel
Motors:	Automotive grade 12V D.C. Stall Torque 15.6 g-cm
	No-load Speed 55.8 rpm
	Rated Output Power 1.42 W
	Stall Protected
Quality and Type of LED's:	10 High Flux LED's
	P-Vex lens technology
	8° beam angle
	Anodized Aluminum heat sink w/liquid powder-cast finish
Peak Beam Intensity:	544,000 Candela
Max Beam Distance:	4,839 ft
Voltage DC:	12V
Power Consumption:	40W
Max Current Draw:	3.7 amps
Wireless Remote Control:	Radio Frequency: 433 MHz
	> 2000 possible address codes with 7 station dip switch
	Transmitter power: A23 12v batteries
	Radio Frequency allows for remote operation up to 80 feet away
	Lamp On/Off , Directional Controls, Speed Selector
Hardwired Dash Control:	Lamp On/Off, Directional Controls
	20' of six wire cord, 10' increments as accessories
Warranty:	3 Year Limited Warranty
Mounting Options:	Permanent Mount, Portable Light/Magnetic Shoe, Portable Light/Permanent Shoe
Rockguard:	Optional Accessory

